

Lette airconditionapparater til erhvervsbrug

Gulv loft

Absolut kontrol og fremragende ydelse!



Central kontrolstyring (valgfri)



Hotelmenu



Forberedt for wi-fi



HEPA-filer



Følg mig



Gylden finne

| Model | | V7KI-18WiFi/ U7RS-18 | V7KI-24WiFi/ U7RS-24 | V7KI-36WiFi/ U7RS-36 | V7KI-50WiFi/ U7RT-50 | V7KI-60WiFi/ U7RT-60 | |
|--|---------------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|------|
| Kølekapacitet (BTU/t.) | | 18.000 (9.250-20.000) | 24.000 (10.990-26.500) | 36.000 (9.300-39.000) | 48.000 (12.000-52.000) | 54.000 (14.000-57.000) | |
| Kølekapacitet (kW) | | 5,28 (2,71-5,86) | 7,03 (3,22-7,77) | 10,55 (2,73-11,43) | 14,07 (3,52-15,24) | 15,83 (4,10-16,71) | |
| Opvarmingskapacitet (BTU/t.) | | 19.000 (8.250-21.500) | 26.000 (9.280-28.285) | 40.000 (9.600-43.600) | 55.000 (14.000-58.000) | 62.000 (15.000-67.000) | |
| Opvarmingskapacitet (kW) | | 5,57 (2,42-6,30) | 7,62 (2,72-8,29) | 11,72 (2,78-12,78) | 16,12 (4,10-17,00) | 18,17 (4,40-19,64) | |
| Sæsonmæssig effektivitet (i henhold til EN14825) | Køling | Pdesign (kW) | 5,4 | 7,2 | 10,5 | 14,0 | 15,5 |
| | | Energiklasse | A++ | A++ | A++ | A++ | A++ |
| | | SEER | 6,2 | 6,1 | 6,2 | 6,1 | 6,1 |
| | Opvarmning (mellemzone) | Pdesign (kW) | 4,0 | 5,5 | 8,6 | 11,2 | 11,9 |
| | | Energiklasse | A+ | A+ | A+ | A+ | A+ |
| | | SCOP | 4,0 | 4,0 | 4,0 | 4,0 | 4,0 |
| | Opvarmning (varm zone) | Pdesign (kW) | 5,1 | 5,8 | 10,0 | 11,7 | 12,6 |
| | | Energiklasse | A+++ | A+++ | A+++ | A+++ | A+++ |
| | | SCOP | 5,1 | 5,1 | 5,1 | 5,1 | 5,1 |
| Spænding/frekvens/fase (V/Hz/F) | | 220-240/50/1 | 220-240/50/1 | 220-240/50/1 | 380-415/50/3 | 380-415/50/3 | |
| Strøminput (A) | Køling | 6,00 (3,20-9,00) | 10,54 (3,90-13,10) | 17,0 (4,2-19,0) | 8,8 (1,9-10,3) | 9,7 (3,2-11,5) | |
| | Opvarmning | 6,60 (2,70-7,30) | 9,50 (3,50-12,70) | 15,0 (3,5-17,5) | 8,9 (2,1-10,5) | 10,5 (2,2-12) | |
| Effektinput (kW) | Køling | 1,45 (0,67-2,03) | 2,30 (0,75-2,93) | 3,90 (0,90-4,25) | 5,00 (0,90-5,95) | 5,65 (1,10-6,65) | |
| | Opvarmning | 1,50 (0,54-1,64) | 2,05 (0,65-2,85) | 3,35 (0,80-3,95) | 5,10 (1,00-6,05) | 6,05 (1,05-7,10) | |
| Luftstrømsmængde (høj/mellem/lav) (m³/t.) | | 958/839/723 | 1.192/1.023/853 | 1.955/1.728/1.504 | 2.100/1.850/1.600 | 2.200/1.950/1.650 | |
| Støjniveau [dB(A)] | Indendørsenhed (lav/mellem/høj) | 24/36,5/41/43,5 | 32/43/46/49 | 37/44/48,5/50 | 36/45/50/53 | 38/46,5/50,5/54 | |
| | Udendørsenhed | 59 | 60 | 63 | 63,5 | 64 | |
| Lydeffektniveau [dB(A)] | Indendørs-/udendørsenhed | 57/65 | 55/66 | 64/68 | 67/73 | 67/73 | |
| Strømforsyningsledning udenders/sikringer (Noxmm²)/(A) | | 3x2,5/1x16 | 3x2,5/1x16 | 3x4,0/1x25 | 5x2,5/3x16 | 5x2,5/3x16 | |
| Signalledninger (Noxmm²) | | 4x1,5 | 4x1,5 | 4x1,5 | 4x1,5 | 4x1,5 | |
| Mål (BxDxH) (mm) | Indendørsenhed | 1.068x675x235 | 1.068x675x235 | 1.650x675x235 | 1.650x675x235 | 1.650x675x235 | |
| | Udendørsenhed | 805x330x554 | 890x342x673 | 946x410x810 | 952x415x1.333 | 952x415x1.333 | |
| Nettovægt (kg) | Indendørs-/udendørsenhed | 28,0/32,5 | 28,0/43,9 | 41,5/66,9 | 41,7/103,7 | 42,3/107,0 | |
| Væskerør Gasrør | | 1/4" 1/2" | 3/8" 5/8" | 3/8" 5/8" | 3/8" 5/8" | 3/8" 5/8" | |
| Kølemiddel/påfyldning (g) | | R32/1.150 | R32/1.500 | R32/2.400 | R32/2.900 | R32/3.000 | |
| Driftstemperaturinterval (°C) Afkøling/opvarmning | | -15-50/-15-24 | -15-50/-15-24 | -15-50/-15-24 | -15-50/-15-24 | -15-50/-15-24 | |