


Kassetter

Ergonomisk design og høj ydelse!



360° luftudtag



Selvstændig svinglamele*



Hotelmenu



Forberedt for wi-fi



Friskluftsindtag



Indbygget afløbspumpe



Model	V7CRI-12WiFiR/ U7RS-12	V7CRI-18WiFiR/ U7RS-18	V7CI-24WiFiR/ U7RS-24	V7CI-36WiFiR/ U7RS-36	V7CI-42WiFiR/ U7RS-42	V7CI-50WiFiR/ U7RT-50	V7CI-60WiFiR/ U7RT-60		
Kølekapacitet (BTU/t.)	12.000 (2.897-14.020)	18.000 (9.900-19.054)	24.000 (11.263-27.000)	36.000 (9.200-39.000)	41.000 (10.000-42.000)	48.000 (12.000-54.000)	53.000 (14.000-57.000)		
Kølekapacitet (kW)	3,52 (0,85-4,11)	5,28 (2,90-5,59)	7,03 (3,30-7,91)	10,55 (2,70-11,43)	12,02 (2,93-12,31)	14,07 (3,52-15,83)	15,24 (4,10-16,71)		
Opvarmingskapacitet (BTU/t.)	13.000 (1.604-14.705)	19.000 (8.100-20.800)	26.000 (9.577-30.500)	38.000 (9.500-42.000)	46.000 (11.500-48.000)	55.000 (14.000-59.000)	62.000 (15.000-68.000)		
Opvarmingskapacitet (kW)	3,81(0,47-4,31)	5,57 (2,37-6,10)	7,62 (2,81-8,94)	11,14 (2,78-12,30)	13,48 (3,37-14,07)	16,12 (4,10-17,29)	18,17 (4,40-19,93)		
Sæsonmæssig effektivitet (i henhold til EN14825)	Køling	Pdesign (kW)	3,5	5,3	7,0	10,5	12,1	15,3	
		Energiklasse	A++	A++	A++	A++	A++	A++	A++
		SEER	6,6	6,3	6,2	6,7	6,1	6,1	6,3
	Opvarmning (mellemsone)	Pdesign (kW)	2,7	4,2	6,0	8,5	9,5	11,0	11,9
		Energiklasse	A+	A+	A+	A+	A+	A+	A+
		SCOP	4,1	4,0	4,0	4,0	4,0	4,0	4,0
	Opvarmning (varm zone)	Pdesign (kW)	3,3	5,4	6,3	10,1	9,8	12,0	12,5
		Energiklasse	A+++	A++	A+++	A+++	A+++	A++	A+++
		SCOP	5,1	4,8	5,1	5,1	5,1	5,0	5,1
Spænding/frekvens/fase (V/Hz/F)	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	220-240/50/1	380-415/50/3	380-415/50/3		
Strøminput (A)	Køling	4,45 (1,32-6,31)	7,20 (3,20-9,20)	10,20 (4,20-12,00)	17,50 (4,20-18,50)	18,80 (3,10-19,10)	8,10 (1,80-10,20)	8,60 (2,10-10,70)	
	Opvarmning	4,73 (1,04-6,07)	6,80 (3,10-8,50)	8,50 (3,60-12,10)	13,50 (3,50-17,50)	16,30 (3,40-19,00)	8,00 (1,90-9,50)	9,60 (2,10-10,70)	
Effektinput (kW)	Køling	1,01 (0,17-1,43)	1,63 (0,72-2,09)	2,32 (0,78-2,75)	3,95 (0,90-4,20)	4,20 (0,68-4,35)	4,65 (0,80-5,90)	5,00 (0,98-6,20)	
	Opvarmning	1,02 (0,12-1,38)	1,54 (0,70-1,93)	1,90 (0,61-2,70)	3,70 (0,75-4,25)	3,70 (0,75-4,25)	4,58 (0,90-5,50)	5,55 (1,20-6,70)	
Luftstrømsmængde (høj/mellem/lav) (m³/t.)	620/510/420	720/620/500	1.300/1.140/1.000	1.700/1.550/1.380	1.900/1.750/1.600	1.970/1.780/1.580	2.000/1.850/1.650		
Støjniveau [dB(A)]	Indendørsenhed (lav/mellem/høj)	25,5/33/36/41	29/35,5/39,5/43	27/39,5/42,5/45,5	39/44,5/47,5/50	38/46/48,5/51	37,5/46,5/48,5/51	40/48/50,5/53	
	Udendørsenhed	53,6	56	60	63	63	63,5	64	
Lydeffektniveau [dB(A)]	Indendørs-/udendørsenhed	56/60	57/63	57/67	63/70	65/71	65/73	65/73	
Strømforsyningsledning udendørs/sikringer (Noxmm²)/V(A)	3x1,5/1x10	3x2,5/1x16	3x2,5/16	3x4,0/1x25	3x4,0/1x25	5x2,5/3x16	5x2,5/3x16		
Signalledninger (Noxmm²)	4x1,5	4x1,5	4x1,5	4x1,5	4x1,5	4x1,5	4x1,5		
Mål (BxDxH) (mm)	Panel	647x647x50	647x647x50	950x950x55	950x950x55	950x950x55	950x950x55	950x950x55	
	Indendørsenhed	570x570x260	570x570x260	830x830x205	830x830x245	830x830x287	830x830x287	830x830x287	
	Udendørsenhed	765x303x555	805x330x554	890x342x673	946x410x810	946x410x810	952x415x1.333	952x415x1.333	
Nettovægt (kg)	Panel-/indendørs-/udendørsenhed	2,5/16,3/26,6	2,5/16,0/32,5	6,0/21,6/43,9	6,0/27,2/66,9	6,0/29,3/71,0	6,0/29,3/103,7	6,0/29,3/107,0	
Væskerør Gasrør	1/4" 3/8"	1/4" 1/2"	3/8" 5/8"	3/8" 5/8"	3/8" 5/8"	3/8" 5/8"	3/8" 5/8"		
Kølemiddel/påfyldning (g)	R32/720	R32/1.150	R32/1.500	R32/2.400	R32/2.800	R32/2.900	R32/3.000		
Driftstemperaturinterval (°C) Afkøling/opvarmning	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24	-15-50/-15-24		